

TRB-220 ROTATING BEACON, HEXAGONAL LENS CAROUSEL CONFIGURATION
Effective Intensity Table for Selected Rotation Periods
(All Calculations were made with the Schmidt-Clausen Method)

LAMP SIZE	HOR. DIV. (deg)	FIXED INT.** (cd)	ROTATION PERIOD / SPEED								
			120 sec / 0.5 rpm	90 sec / .666 rpm	72 sec / .833 rpm	60 sec / 1.0 rpm	48 sec / 1.25 rpm	40 sec / 1.5 rpm	30 sec / 2.0 rpm	24 sec / 2.5 rpm	
12 V / 10 W On-Time, Sec	1.60°	42,724	21,987 0.533	18,936 0.400	16,616 0.320	14,803 0.267	12,724 0.213	11,157 0.178	8,952 0.133	7,475 0.107	
12 V / 20 W On-Time, Sec	1.53°	109,561	58,509 0.51	50,670 0.383	44,652 0.306	39,912 0.255	34,438 0.204	30,285 0.170	24,400 0.128	20,430 0.102	
12 V / 35 W On-Time, Sec	1.93°	169,903	104,364 0.643	92,516 0.483	83,033 0.386	75,313 0.322	66,111 0.257	58,914 0.214	48,379 0.161	41,040 0.129	
12 V / 50 W On-Time, Sec	1.90°	241,131	145,260 0.633	128,321 0.475	114,848 0.380	103,935 0.317	90,993 0.253	80,916 0.211	66,245 0.158	56,077 0.127	
12 V / 75 W On-Time, Sec	2.35°	238,643	148,914 0.783	132,388 0.588	119,092 0.470	108,223 0.392	95,214 0.313	84,997 0.267	69,979 0.196	59,471 0.157	
12 V / 100 W On-Time, Sec	2.40°	367,823	238,459 0.800	213,526 0.600	193,204 0.480	176,414 0.400	156,105 0.320	139,990 0.267	116,032 0.200	99,077 0.160	

LAMP SIZE	HOR. DIV. (deg)	FIXED INT.** (cd)	ROTATION PERIOD / SPEED							
			20 sec / 3.0 rpm	15 sec / 4.0 rpm	12 sec / 5.0 rpm	10 sec / 6.0 rpm	9 sec / 6.66 rpm	8 sec / 7.5 rpm	7 sec / 8.57 rpm	6 sec / 10.0 rpm
12 V / 10 W On-Time, Sec	1.60°	42,724	6,416 0.089	5,000 0.067	4,096 0.053	3,469 0.044	3,150 0.040	2,821 0.036	2,489 0.031	2,151 0.027
12 V / 20 W On-Time, Sec	1.53°	109,561	17,571 0.085	13,729 0.064	11,265 0.051	9,551 0.043	8,680 0.038	7,777 0.034	6,867 0.030	5,938 0.026
12 V / 35 W On-Time, Sec	1.93°	169,903	35,635 0.107	28,205 0.080	23,339 0.064	19,905 0.054	18,143 0.048	16,306 0.043	14,443 0.038	12,530 0.032
12 V / 50 W On-Time, Sec	1.90°	241,131	48,615 0.106	38,397 0.079	31,728 0.063	27,033 0.053	24,627 0.048	22,122 0.042	19,584 0.037	16,981 0.032
12 V / 75 W On-Time, Sec	2.35°	238,643	51,707 0.131	41,000 0.098	33,968 0.078	28,994 0.065	26,439 0.059	23,773 0.052	21,067 0.046	18,285 0.039
12 V / 100 W On-Time, Sec	2.40°	367,823	86,445 0.133	68,881 0.100	57,249 0.080	48,978 0.067	44,714 0.060	40,254 0.053	35,716 0.047	31,040 0.040

- **NOTES: (1) All fixed intensities were measured with the outer glazing in place.
(2) The Schmidt-Clausen Formula is used in compliance with IALA's "Recommendation for the Calculation of the Effective Intensity of a Rhythmic Light", November 1980.
(3) Intensities may be reduced due to shadowing when using a 6-place lampchanger by approximately 20% at two small arcs 180° apart.

SPECIFICATIONS

Power Consumption
Lamp As specified (from 3 to 110 W)
Motor Average 2.5 W

Power Input
DC Version 9 – 36 VDC
AC Version (requires additional equipment) 110 – 240 VAC, 50/60 Hz

Lampchanger Tideland TF-3B OMNIBUS II, high temperature, 3- or 6-place lampchanger, as specified

Drive System Brushless DC motor; gearless direct drive

Optics
Acrylic Moulded Flash Panel 110 mm focal length, Dioptric-Catadioptric Fresnel Lens (available in clear, red, green, yellow and opaque)

Glazing 330 mm UV-resistant acrylic

Lens Configuration
Standard 220 mm Hexagonal
Optional 220 mm Octagonal

Ventilation Not required (up to 110 W lamp)

Rotation Periods 16 rotation periods; field-selectable
Standard Periods 120, 90, 72, 60, 48, 40, 30, 24, 20, 15, 12, 10, 9, 8, 7 and 6 seconds

Environmental
Temperature -40°C to +55°C
Humidity 100% non-condensing

Physical Size
Height 851 mm (33.5 in) with Spike
Weight 20.5 kg (45 lb)

NOTE: Specifications are subject to change.



TIDELAND SIGNAL CORPORATION
CORPORATE HEADQUARTERS

P.O. Box 52430
Houston, Texas 77052-2430, USA
4310 Directors Row
Houston, Texas 77092 USA
PH: + 1 713-681-6101
FAX: + 1 713-681-6233
E-MAIL: hq@tidelandsignal.com

P.O. Box 52370, O.C.S.
Lafayette, Louisiana 70505-2370, USA
PH: + 1 337-269-9113
FAX: + 1 337-269-9052
E-MAIL: lafayettesales@tidelandsignal.com

TIDELAND SIGNAL CANADA LTD.
#2170-21331 Gordon Way
Richmond, B.C., Canada V6W 1J9
PH: + 1 604-247-0988
FAX: + 1 604-247-0987
E-MAIL: sales@tidelandsignalcanada.com

TIDELAND SIGNAL PTE. LTD.
Crystal Time Building
16 Tannery Lane #04-00
Singapore 347778
PH: + 65 6333-0078
FAX: + 65 6333-0079
E-MAIL: sales@tidelandsignal.com.sg

TIDELAND SIGNAL LIMITED
Unit B, Kendal House
Victoria Way
Burgess Hill, Sussex, RH15 9NF, UK
PH: + 44 (0) 1444 872240
FAX: + 44 (0) 1444 872241
E-MAIL: sales@tidelandsignal.ltd.uk

TIDELAND SIGNAL LTD. (UAE)
FZS1 BB03, JAFZA South
Jebel Ali Free Zone, Dubai, U.A.E.
PH: + 971 4-886-0180
FAX: + 971 4-886-0181
E-MAIL: sales@tidelandsignal.ltd.uk

WEB SITE: www.tidelandsignal.com



Tideland Signal Corporation maintains ISO 9001:2000 accreditation. It is company policy to provide products and services that meet the highest standards of quality in the industry.

Membership Organisations



PRINTED IN U.S.A.

© Tideland Signal Corporation 2006 – 5MB13R2