

# SB-1000

## Sentinel® Multi-purpose Buoy

---

SB-1000 is a product of Tideland's continued development of high performance, low maintenance, cost effective, multipurpose buoys. The unique design of the buoy allows it to be deployed in a variety of applications that include shallow water, channel edges, rivers up to 4 knots current, marinas and harbours.



### CHARACTERISTICS

- UV-stabilised polyethylene – rotationally moulded to form a seamless hull, 9.5mm thick, able to withstand knocks and/or collisions. Through a unique mould design and a controlled process, an increased thickness is formed at major stress points. This rugged material is abrasion resistant and reduces marine growth. Polyethylene eliminates the need for costly sandblasting and painting.
- Long-term strength – equipped with a stainless steel mooring and lifting eye, the buoy is easily handled. SB-1000 buoy is Polyurethane foam filled to prevent water ingress in event of a puncture. As with all Sentinel® buoys, minor punctures are on-station repairable.
- Colours – SB-1000 is available in all recommended IALA colours.
- Now with replaceable mooring and lifting eyes to comply with the latest IALA Guidelines.
- Lantern – A SolaMAX-3 (or similar) can be fitted to the top for nighttime applications.



# SB-1000

Sentinel® Multi-purpose Buoy

<b>Construction</b>	Rotationally moulded in medium density UV-stabilised virgin polyethylene, 9.5mm thick
<b>Foam Filling</b>	Polyurethane foam
<b>Air Weight</b>	122kg (268lb)
<b>Diameter</b>	1000mm (39in)
<b>Focal Plane Height</b>	1633mm (64in)
<b>Draft</b>	478mm (19in)
<b>Freeboard</b>	274mm (11in)
<b>Submergence</b>	8Kg/cm (45lb/in)
<b>Surface Colour</b>	As Specified
<b>Radar Reflector</b>	10m <sup>2</sup>
<b>Maximum Mooring Load</b>	227Kg (500lb)
<b>Maximum Current</b>	4 knots

## SB-1000 Mooring Table for Currents of Less than 2 Knots

Water Depth	Chain Length	Chain Size	Sinker Air Weight
2.5m	6m	3/4"	80kg
5m	10m	3/4"	85kg
7.5m	15m	5/8"	95kg
10m	18m	5/8"	100kg
12.5m	25m	1/2"	105kg
15m	30m	1/2"	115kg
20m	35m	1/2"	125kg

Recommendation is to use a 250kg minimum sinker for above conditions.

# SB-1000

Sentinel® Multi-purpose Buoy

## SB-1000 Mooring Table for Currents of Less than 4 Knots

Water Depth	Chain Length	Chain Size	Sinker Air Weight
2.5m	11m	3/4"	295kg
5m	20m	5/8"	320kg
7.5m	35m	1/2"	345kg
10m	40m	1/2"	375kg
12.5m	45m	1/2"	400kg
15m	50m	1/2"	425kg
20m	60m	1/2"	475kg

Recommendation is to use a 500kg minimum inker for above conditions. (650kg for 15 to 20m).

