

DC (Solar) IECEX Zone 2 Nav aids

Universal Navigational Aids Systems

Tideland have created a suite of SOLACHAN[™] products specifically to meet the exacting needs of Saudi Aramco for marking of their new and existing Offshore installations. These products fulfil the requirements for their AC supported and DC (Solar) systems but are equally suited to other similar applications. IECEX Zone 2 Certified DC Solutions are designed to comply with International IECEX Certification Standards and exceed the Certification of existing Saudi Aramco Nav aids installations. The IECEX Solution is the highest specification of the suite of products designed for Saudi Aramco. They provide the same performance of the other variants but include a higher certification level in comparison to existing hazardous area installations. An IECEX Zone 2 Certified version of Tideland's NOVA-65 Lantern is used for this application and consists of an epoxy painted alloy housing and toroidal lens with integral photocell, to provide a 5 Nautical Mile Range as standard. The IECEX Certification limits the lens divergence to 10 degrees only which slightly increases overall power consumption and does not allow for a 10 mile range option. The metal housing also prevents this version from being fitted with GPS Synchronisation so only Hard Wire Synchronisation may be used. The lights run independently from the 12v 165Ah VRLA Gel Battery which provides the best possible power source for very small, long duration loads such as Nav aids. The Battery is maintained by a small 12v battery charger housed in the weatherproof Exd Enclosure.



TECHNICAL

- Suitable for Zone 2 Hazardous Areas.
- Maintenance free Tideland Nova-65 IECEX 10 degree lantern (5NM Standard)
- 12v 165Ah Gel Battery in IECEX Certified Painted Stainless Steel Enclosure
- 12v Solar Voltage Regulator in Exd Painted Alloy Enclosure with AC/Battery Circuit Breakers
- 12v 50w or 12v 108w IECEX Solar Module on fully adjustable bracket
- Wired with GSWB Fire Resistant Cables and Nickel Plated Brass Cable Glands
- Pedestals Galvanised Steel and Painted to APCS-26T (EU) in RAL 1023 Yellow
- Hard Wire Sync Only
- >280 Days Autonomy for standard light at Morse U 15s

CHARACTERISTICS

- Separated Power and Sync field cable Junction boxes for safety
- Solar Powered Stand Alone – No External Power required
- 360 Degree Rotation of Charger/Junction Box Panel and Solar Module Possible
- kit is also available to convert the DC (Solar Powered) Stations to AC Stations by replacing/adding just 3 components. A kit is also available to convert from AC to DC variants

DC (Solar) IECEX Zone 2 Nav aids

Universal Navigational Aids Systems

